Advance your business prospects.

imageRUNNER ADVANCE C9000 PRO Series Enter a groundbreaking world of added opportunity with Canon's new imageRUNNER ADVANCE PRO Light Production colour range. Combining excellent image quality, high-end finishing and powerful workflow integration, we're proud to introduce our most advanced Light Production engines to date.

For short-run colour and complex jobs ondemand, the route to extra profit has just arrived.

UP TO **70ppm**COLOUR AND
MONO

CHOICE OF 2 FIERY RIPS

MIXED MEDIA SUPPORT

LARGE PAPER CAPACITY

SADDLE FINISHER AND TRIMMER

MODULAR



High quality

- Stable and consistent colour output using technology from our imagePRESS range
- 1200dpi printing

High productivity

- Up to 70ppm colour and mono
- Produce short run complex jobs easily
- Choice of 2 Fiery RIPs
- Large paper capacity
- Load while run capability

Robust finishing accessories

- Professional Puncher
- Multi-Inserter
- Multi-Folding Unit
- Booklet Finisher & optional Inner Trimmer
- Staple Finisher

Versatility

- Easy integration with existing infrastructure
- Mixed media support coated and uncoated
- Paper weights up to 300gsm
- Max standard paper size SRA3
- Max irregular paper size 330.2 x 487.7mm





Specification: imageRUNNER ADVANCE C9070 PRO / C9060 PRO

Paper Deck Unit-A1

Type Maximum Original Size Copy Sizes Resolution Copy/Print Speed Max speed by paper weight Magnification First copy time Warm-Up Time Duplexing Paper weight Paper Capacity CPU Memony Hard Disk Drive Interface Power Supply Power Consumption Dimensions (WoXbH)	Cassette 1.2 Cassette 3.4 Stack Bypass Reading Copying Printing A4 (80 gsm) C9070 PRO A4 A3 Zoom Fixed Black-and-White Full Colour 70pm model Multiple Copies /Prints Cassette Stack Bypass Duplex Standard Paper Deck Total capacity	Console (Reader/Printer separated) A3 A4 A5R-SRA3 (320 x 450mm), 13"x19"(330 x 483mm) A5R-SRA3 (320 x 450mm), 13"x19"(330 x 483mm) Free size 100 x 148mm to 330,2 x 487.7mm Envelopes (DI, ISO-BS, ISO-C5) 600dpi x 600dpi 600dpi x 600dpi 1200dpi x 1200dpi (text/line) 256 Gradations C9070 PRC: 70ppm (B&W/Colour) C9060 PRC: 60ppm (B&W/Colour) Plain A4 52-105gsm: 70ppm 106:-220gsm: 35ppm 221-300gsm: 23.3ppm Coated: 106-180gsm: 21.6ppm/35ppm depending on mode 52-105gsm: 17.5ppm colour, 18.8 b/w 221-300gsm: 17.5ppm colour, 18.8 b/w 221-300gsm: 21.6ppm/35ppm (B&W/Colour) Plain A4 52-105gsm: 35ppm colour, 18.5 b/w 106:-220gsm: 17.5ppm colour, 12.5 b/w Coated paper (106:300gsm) 10.8ppm (B&W/Colour) Plain A4 52-105gsm: 32.5ppm 221-300gsm: 21.6ppm 63-220gsm: 32.5ppm 221-300gsm: 21.6ppm 52-105gsm: 32.5ppm 221-300gsm: 21.6ppm 52-105gsm: 16.3ppm 221-300gsm: 16.3ppm 52-105gsm: 10.8ppm Coated 106-180gsm: 10.8ppm Coated apper (106:300gsm) 10.8ppm (B&W/Colour) 25-400% 25%, 50%, 71%, 100%, 141%, 200%, 400% 70ppm model: 4.4sec 60ppm model: 6.6 6 minutes 5 minutes 1 to 9999 sheets 5 standard automatic stackless 5 2 to 220gsm 5 2 to 220gsm 5 2 to 220gsm 5 2 to 300gsm 5 2 to 500gsm 5 2 to 500gsm 5 50 sheets x2 cassettes (80gsm) 550 sheets x2 cassettes (80gsm)
Print Specification imagePASS-AT PDL Resolution Hard Disk CPU PS Fonts PCL Fonts Supported OS Interface Network Protocol ColorPASS-GX300 PDL Resolution Memory Hard Disk CPU PS Fonts Supported OS Interface Network Protocol ColorPASS-GX300 PDL Resolution Memory Hard Disk CPU PS Fonts PLC Fonts Supported OS Interface Network Protocol Duplex Color Image Reader Unit-A1 Paper size Paper weight Max. Number of originals Document Scanning speed (max.)		Approx. 288 kg (with 1PDS & Upright Control Panel) PCL5c/ 6, Adobe PostScript 3 1200dpi x 1200dpi, 600dpi x 600dpi 512MB+512MB(Option) 80GB CPU Intel Core Duo T2500 2.0GHz 136 Adobe PS Fonts 80 Agfa fonts Windows 2000/XP/Server2003/Server2008/Win7/Vista/ Vista SP1, Mac OSX (10.3.9 or later) Ethernet 1000Base-T7/100Base-T7), USB TCP/IP (LPD/Port9100/IPP/SMB/FTP), AppleTalk Adobe PostScript 3 1200dpi x 1200dpi, 600dpi x 600dpi 2GB 160GB Intel Core2 Duo Xeon E8400 2x3.0Ghz 136 Adobe PS Fonts N/A Windows 2000/XP/Server2003/Server2008/Vista/Vista SP1, Mac OSX (10.3.9 or later) Stehernet 1000Base-T7/10Base-T7), USB, D-sub 15-pin connector TCP/IP (LPD/Port9100/IPP/SMB/FTP), AppleTalk A3, A4, A4R, A5, ASR 42 to 220gsm S0 to 220gsm (B8W), 64 to 220gsm (Colour) 300 Sheets (80gsm) A4 120jpm 600dpi (B8W), 70jpm 600dpi (Colour) A4 120jpm 600dpi (B8W), 70jpm 600dpi (Colour) A4 120jpm 600dpi (B8W), 140jpm 300dpi (Colour) A5S x 590 x 262mm Approx 38.9kg

Paper Deck Unit-A1 Paper Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight		A4 52 to 220gsm 3,500 sheets (80gsm) 323 x 583 x 570mm Approx. 37kg
POD Deck Lite-A1 Paper Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight		A3, A4, A4R, SRA3, 13"x19" 52 to 300gsm 3,500 sheets (80gsm) 601 x 621 x 570mm Approx. 50kg
Multi-drawer Paper Deck-A1 Paper Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight		A3, A4, A4R, A5R, SRA3, 13"×19" 52 to 300gsm 6,000 sheets (80gsm) 950 x 797 x 1040mm Approx. 150kg
Staple Finisher-A1/ Booklet Finisher-A1 Number of trays Tray capacity (Non Collate) Punching Staple position Staple capacity(64-80gsm) Booklet Stitch Specifications (Booklet Finisher only) Paper size: Staple capacity: Paper weight: Dimensions Weight	Tray A: Tray B: Tray C:	3 trays A4/ASR 1,500 sheets, A3/A4R /SRA3/13"x19" 750 sheets A4 2,500 sheets, A5R 1,250 sheets, A3/A4R/ SRA3/13"x19" 750 sheets A4/ASR 250 sheets, A3/A4R 125 sheets, SRA3/13"x9" 30 sheets Optional 2/4 hole punching Corner, Double, Booklet Stitch (Booklet Finisher only) 100 sheets (80gsm) A3, A4R, SRA3, 13"x19" 20 sheets (80 pages, 64-80gsm) Body paper 52 to 105gsm, Cover pager 52 to 300gsm Staple Finisher-A1: 782 x 765 x 1040 Booklet Finisher-A1: Approx.61 kg Booklet Finisher-A1: Approx.61 kg Booklet Finisher-A1: Approx.61 kg Booklet Finisher-A1: Approx.61 kg
Inner Booklet Trimmer-A1 One Edge Trimming (Fore-edge) Trim Width Trim Thickness Acceptable Paper Weight Weight Approx		2-20mm Up to 20 sheets (includes Cover) 52 to 300gsm 32kg
Document Insertion Unit-H1 Numbers of trays Paper Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight		2 trays A3, A4, A4R, SRA3, 13"×19", Free size (139.7 x 182mm to 330.2 x 487.7mm) 52 to 300gsm 200 sheets x 2 tray 746 x 793 x 1407mm Approx. 61kg
Paper Folding Unit-G1 Z-Fold C-Fold Double parallel Half fold Dimensions Weight	Paper Size: Paper Weight: Paper Size: Paper Weight: Paper Size: Paper Weight: Paper Size: Paper Weight: Paper Weight:	30 sheets A3, 10 sheets A4R 52 to 105gsm 40 sheets A4R 52 to 105gsm 25 sheets A4R 52 to 90gsm 30 sheets A3, 10 sheets A4R 52 to 105gsm 336 x 793 x 1190mm Approx. 71kg
Professional Puncher-C1 External In-line Punch Unit Acceptable Punch Paper Weight Acceptable Punch Paper Size Punch Tools Dimension Weight		75-216gsm (Plain paper), Pro Click: 75-176gsm A4 Plastic Comb 21-Hole Twin Loop 23-Hole(Round) Twin Loop 34-Hole(Round) Color Coil 47-Hole Velo Bind 12-Hole Loose Leaf 4-Hole Punch Loose Leaf 4-Hole Punch Loose Leaf 3-Hole Pro Click 34-Hole 305 x 792 x 1040mm Approx. 80kg
Professional Puncher Integration Unit-B1 Dimension Weight		250 x 792 x 1040mm Approx. 40kg
Optional Accessories	Printer Cover-B1, Stamp Ink Cartridge-C1, ADF Access Handle-A1, Data Erase KiF-C1, HDD Data Encryption & Mirroring KiF-C1, Secure Watermark-B1, Web Access Software-H1, Access Management system KiF-B1, 80GB HDD-A1, 1TB HDD-B1, Removable HDD KiF-AB1, Document Scan Lock KiF-A1, Super G3 Fax Board-AD1, Super G3 Tad Line Fax Board-AD1, Universal Send Advanced Feature Set-D1, Universal Send Digital User Signature KiF-C1, Remote Fax KiF-A1, Paper Deck Double Feeding Detection KiF-A1, Punch Unit-BG1 (2/4 hole), Punch Unit BH1 (Swedish 4 hole), Utility Tray-A1, Key Wirtch Unit-B1, Copy Card Reader Attachment-A1, Card Reader-C1, Remote Operations Software KiF-B1, Voice Guidance KiF-F1, Voice Operation KiF-C1, Multimedia Reader/Writer-A1, Serial Interface KiF-K1, Copy Control Interface KiF-A1	











www.canon.com

Canon Europa www.canon-europe.com

English-UK Edition 0138W931 © Canon Europa 2009 (0909) Canon (UK) Ltd Woodhatch, Reigate Surrey RH2 8BF Tel: 01737 220000 Fax: 01737 220022 www.canon.co.uk

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods This leaflet and the specifications of the product have been developed prior to the date of product launch. Final are subject to change without notice. ³⁸ and 69. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

> Canon Ireland Arena Road, Sandyford Industrial Estate Dublin 18, Ireland Tel: 01 2052400 Fax: 01 2958141 www.canon.ie

